


INCLUDE INSALLATION INSTRUCTIONS FOR
DESUPERHEATING HEAT EXCHANGER

NORMALLY MOUNTED IN VERTICAL POSITION WITH
GAS IN AT TOP

POWDER COAT BLACK

U.L. & C.U.L. IDENT. RR 5839
REFRIG. SIDE WP. 500 psig. WATER SIDE WP. 150 psig.
CONTROL No. 15H9 FILE No. SA6300

| | | | | | | | | | |
|--|------|------|-------|--------------------------|--|---|--|---|-------------------------|
| TOLERANCES NOT SPECIFIED FRACTIONS ± 1/16 DECIMALS ± .0625 ANGLES ± 2.5° | | | | <div>REFRIGERATION</div> | | <div>RESEARCH</div> <small>INC.</small> | |  POINTING THE WAY | |
| | | | | BRIGHTON, MICHIGAN | | | | | |
| NO. | DATE | CH'D | APP'D | REVISIONS | | MATERIAL | | | |
| | | | | | | NAME 10 H.P. DESUPERHEATING HEAT EXCHANGER | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | DRAWN BY: MJH | | SCALE 1 : 2 | DRAWING NO. 5839 |
| | | | | | | CHK'D JBN | | DATE 01/23/13 | |
| | | | | | | CUT L. | | APP'D JBN | |